

INSTALLATION METHOD FOR HEAD STUD KITS

Part Number: 234-4339 Application: RHS Aluminum block w/ RHS LS7 heads

- Always verify the part number for your application with the part number on the side of box and the part number on the instruction sheet. This will help ensure you have the correct installation procedure for your specific application before installing any components.**
- Clean and inspect all hardware prior to installation. Look for obvious defects or shipping damages, plus proper fit, length and dimension.
- To ensure proper thread engagement and accurate torque readings, clean ALL threads in the block. Chase if necessary with ARP Thread Chaser, part number 912-0011 (M11 X 2.0) and 912-0001 (M8 X 1.25).
- If the cylinder head studs protrude into a water jacket, lubricate the block threads of the studs with ARP THREAD SEALER.
- Screw four 8mm (2.600 in. long) studs into the bottom of each cylinder head.
- Screw the remaining studs into the block "HAND TIGHT ONLY". Please refer to the head stud and washer mounting location chart and the bolt torque sequence diagram listed below.
NOTE: LOCTITE MAY BE USED IF A PERMANENT MOUNTING OF THE STUDS IS PREFERRED. THE FASTENERS, HOWEVER, MUST BE TORQUED PRIOR TO THE LOCTITE SETTING UP.
- Install the cylinder head(s) and check for binding or misalignment.
- Lubricate the stud threads and the nuts with ARP ULTRA-TORQUE FASTENER ASSEMBLY LUBRICANT. Then install the nuts onto the studs and tighten them hand tight. ARP recommends using the ARP ULTRA-TORQUE FASTENER ASSEMBLY LUBRICANT that is provided with each kit as opposed to motor oil. This is due to higher friction on the studs as well as inconsistencies in the clamping force of the fasteners when motor oil or other low quality lubricants are used.

PRELOAD (TORQUE) RECOMMENDATIONS

- Following the manufacturers recommended torque sequence tighten the nuts in three equal steps to the following specifications with ARP ULTRA-TORQUE FASTENER ASSEMBLY LUBRICANT.

M11 90 ft lbs

M8 28 ft lbs

Note: ARP Ultra-Torque Fastener Assembly Lubricant has been specifically designed to reduce tension preload scatter and eliminate the need to cycle high performance engine fasteners before final installation. ARP Ultra-Torque far surpasses all requirements offered by previous ARP lubricants in terms of fastener preload repeatability and performance lubricating properties. For more information on ARP Ultra-Torque visit our website at www.arp-bolts.com or call 1 800-826-3045.

Head Stud and washer mounting locations

- #1-8 in torque sequence – M11 X 5.150 in. long w/.875 O.D. washer**
- #9 &10 in torque sequence - M11 X 5.250 in. long w/.875 O.D. washer**
- #11-15 in torque sequence – M8 X 2.725 in. long w/.550 O.D. washer**
- #16-19 in torque sequence – M8 X 2.725 in. long w/.675 O.D. washer**
- #20-23 in torque sequence – M8 X 2.600 in. long w/.550 O.D. washer**

(Studs #20 thru 23 screw into the bottom of the cylinder head and protrude into the lifter valley once the head is installed)

